

CHEMGROUT CG-050 GROUT PUMP

The ChemGrout model CG-050 is a portable, skid mounted, air or hydraulic powered grout pump. The lightweight aluminium construction makes this model portable for hard to reach jobs. The holding hopper is connected directly to the suction of the grout pump to provide a continuous pumping operation. The grout pump is a 2" positive displacement, pulsating piston. This grout pump is available with either an air or hydraulic cylinder to power the pump. All components are easily accessible for operating, cleaning and maintenance. The pump comes complete and ready to use with a 3.8m grout hose and a set of spare piston cups.

APPLICATION

Marine/underwater, hollow metal filling, door frames, window frames, precast, machine base, undersealing, slab raising, and encasements.



SPECIFICATIONS

MODEL NUMBER	PISTON PUMP MODEL	POWER	HOPPER	MAX OUTPUT	MAX PRESSURE
CG050	2" Piston Pump	Air	19 litres	19 lpm	225 PSI (16 Bar)
CG050/H	2" Piston Pump High Pressure	Hyd.	19 litres	19 lpm	400 PSI (28 Bar)

REQUIREMENTS, WEIGHTS, AND DIMENSIONS

MODEL NUMBER	DESCRIPTION/REQUIREMENTS	DIMENSIONS (m)	WEIGHT (kg)
CG050	Skid Mounted Air Pwd. Requires 15 CFM, 100 PSI	1.1 L X 0.27 W X 0.6 H	25
CG050/H	Skid Mounted Hyd. Pwd. Requires 5 GPM, 1000 PSI	1.1 L X 0.27 W X 0.6 H	43

EXPERTISE YOU CAN DEPEND ON



📍 NSW

☎ +61 24902 8080

🌐 www.ausdrillingattachments.com.au

REPAIRS AND SERVICE

✉ repairs@ausdrillingattachments.com.au

SALES

✉ sales@ausdrillingattachments.com.au