

ALMINCO - PORTABLE GROUT PUMP AND MIXERS

The Alminco pneumatic Grout Mixer Motor and Bowl and the GB7 series of reciprocating, single piston grout pumps are designed to meet the demanding conditions of the mining, civil and construction industries.

GROUT PUMP SPECIFICATIONS

- No exposed aluminium
- Non-sparking, nylon polymer body, with a stainless-steel riser tube

MODEL	GB7	DIVORCED	LOW PRESSURE
Motor piston (dia mm)	150	150	150
Weight (kg)	18	20.6	21.5
Length (mm)	1080	1180	1180
Average flow rate (L/m)	60	64	23
Stall pressure (psi)	400	400	450
Maximum air supply (m3/h)	50	50	50
Discharge port bsp	32	32	25



GROUT BOWL AND MIXER MOTOR SPECIFICATION AND FEATURES

MODEL	MKIV	WEIGHT AND DIMENSION	
Capacity (L)	150	Total height (incl. mixers) (mm)	1025
Power (kW)	1.94	Bowl height (mm)	600
Maximum free speed (RPM)	650	Bowl diameter (mm)	600
Stall torque (Nm)	200	Dru weight (incl. motor) (kg)	79

- Steel mesh guard with dual latches
- Inline oil lubricator
- Air lockable valve

Optional accessories include: hoses, packers, whip checks, spare parts, and fittings. A comprehensive Plant Safety File is available upon request, including reports and training documents.

Hire, service, and repair is also available. Please contact our team.



EXPERTISE YOU CAN DEPEND ON



📍 NSW

☎ 02 4092 8080

🌐 www.ausdrillingattachments.com.au

REPAIRS AND SERVICE

✉ repairs@ausdrillingattachments.com.au

SALES

✉ ada@ausdrillingattachments.com.au