



M2200 Pan Mixer

2200 / 3000 lb Heavy-Duty Electric/Hydraulic Power Pan Mixer



- 3,000 lb concrete / shotcrete batch capacity –(3 minute mix time 2200 lb bag) (subject to density of material)
- Variable Speed Mixer Blade Rotation - 59 RPM maximum
- Hydraulic Motor Drive, Torque 13762 Nm (Variable Displacement Hydraulic Piston Pump (displacement 71cc))
- Single Easy to Clean Discharge Door
- NEMA 4 Weatherproof Control Panel on Operator Platform
Power On-Off, Mixer Stop-Start, E-Stop, Horn-Reset, Mixer RPM Control, Primary Discharge Open-Close, CleanOut Discharge Open-Close, CleanOut Tilt Up-Down, Hydraulic pressure gage and Amp meter
- Work Platform with Control Box and Safety Railing
- Quick Disconnects (Hydraulic, Electrical) for ease of set-up and clean-up
- ForkLift Tubes and Lifting Eye Kit On Mixer for Easy Lifting and Transport
- Optional Stainless Steel Water Tank for Precise Water Measurement (+ optional flow meter)
- Optional Pressure Washer (3 gpm flow, 2000 psi, hydraulic)



Optional 50HP Electric Power Pack (above) Slides Under Mixer for Transport

Dimensions: Width: 86" (7 ft, 2 inches)

Height Minimum: 102" (8 ft, 6 inches) (when collapsed for transport (bag splitter can be removed to reduce height 22" further)

Height Maximum: 154" (12 ft, 11 inches) (for operation at max height)

Minimum clearance under discharge door: 67" (1701mm)

Maximum clearance under discharge door: 99" (2515mm)

Weights: Mixer: 7300 lb (3312kg), PowerPack 2300 lb (1044kg)(estimates)

AUSTRALIAN DRILLING ATTACHMENTS (ADA)

52 Enterprise Drive BERESFIELD NSW 2322

+61 4092 8080 | www.drillplus.com.au | ada@drillplus.com.au